


## The Palm Bay--Melbourne, FL, Urbanized Area Rapid Ecosystem Analysis for 1992



Land cover areas are in acres

**Total Tree Canopy: 14,222 acres (10.0%)**

### Air Pollution Removal

By absorbing and filtering out nitrogen dioxide (NO<sub>2</sub>), sulfur dioxide (SO<sub>2</sub>), ozone (O<sub>3</sub>), carbon monoxide (CO), and particulate matter less than 10 microns (PM<sub>10</sub>) in their leaves, urban trees perform a vital air cleaning service that directly affects the well-being of urban dwellers. CITYgreen estimates the annual air pollution removal rate of trees within a defined study area for the pollutants listed below. To calculate the dollar value of these pollutants, economists use "externality" costs, or indirect costs borne by society such as rising health care expenditures and reduced tourism revenue. The actual externality costs used in CITYgreen of each air pollutant is set by the each state, Public Services Commission.

Nearest Air Quality Reference City: ,

|                     | <u>lbs. Removed</u> | <u>Dollar Value</u> |
|---------------------|---------------------|---------------------|
| Carbon Monoxide:    | 63,387              | \$27,051            |
| Ozone:              | 735,291             | \$2,256,637         |
| Nitrogen Dioxide:   | 139,452             | \$427,983           |
| Particulate Matter: | 570,484             | \$1,168,089         |
| Sulfur Dioxide:     | 304,258             | \$227,920           |
| <b>Totals:</b>      | <b>1,812,872</b>    | <b>\$4,111,036</b>  |

### Carbon Storage and Sequestration

Trees remove carbon dioxide from the air through their leaves and store carbon in their biomass. Approximately half of a tree's dry weight, in fact, is carbon. For this reason, large-scale tree planting projects are recognized as a legitimate tool in many national carbon-reduction programs. CITYgreen estimates the carbon storage capacity and carbon sequestration rates of trees within a defined study area.

**Total Tons Stored: 611,309**

**Total Tons Sequestered (Annually): 4,759**

## Stormwater

Trees decrease total stormwater volume and slows peak flow; both help cities to manage their stormwater and decrease detention costs. CITYgreen assesses how land cover, soil type, slope, and precipitation affect stormwater runoff volume, time of runoff concentration, and runoff peak flows. It calculates the volume of runoff in a 2-year 24-hour storm event that would need to be contained by stormwater facilities if the vegetation were removed. This volume multiplied by local construction costs calculate the dollars saved by the tree canopy. CITYgreen uses the TR-55 model developed by the Natural Resource Conservation Service (NRCS) which is very effective in evaluating the effects of land cover/land use changes and conservation practices on stormwater runoff. The infiltration percentage in the report estimates the change in ground water recharge given the change in landcover in this analysis.


### Water Quantity (Runoff)

2-yr, 24-hr Rainfall: 4.75 in.

Rainfall Distribution Type: III

|  |                     |                 |
|--|---------------------|-----------------|
| Curve Number based on data:  | <b>88</b>           |                 |
| Curve Number after tree removal:   | <b>98</b>           | <u>% change</u> |
| Runoff:  | -9                  |                 |
| Time of Concentration:   | 12                  |                 |
| Peak Flow:   | -18                 |                 |
| Potential for Infiltration:  | 20                  |                 |
| Additional Storage volume needed<br>(to mitigate the change in peak flow): | 44,928,807 cu. ft.  |                 |
| Construction cost per cu. ft.:   | \$2.00              |                 |
| <b>Total Stormwater Savings:</b>   | <b>\$89,857,614</b> |                 |


**Annual costs based on payments  
over 20 years at 6% interest:** **\$7,834,196 per year**





### Water Quality (Contaminant Loading)

Cities must comply with Federal clean water regulations and develop plans to improve the quality of their streams and rivers. Trees filter surface water and prevent erosion, both of which maintain or improve water quality. Using values from the US Environmental Protection Agency (EPA) and Purdue University's L-thia spreadsheet water quality model, The Natural Resources Conservation Service (NRCS) developed the CITYgreen water quality model. This model estimates the change in the concentration of the pollutants in runoff during a typical storm event given the change in the land cover. This model estimates the Event Mean Concentrations of Nitrogen, Phosphorus, Suspended Solids, Zinc, Lead, Copper, Cadmium, Chromium, Chemical Oxygen Demand(COD), and Biological Oxygen Demand (BOD). Pollutant values are shown as a percentage of change.

**Percent Change in Contaminant Loadings**



## The Palm Bay--Melbourne, FL, Urbanized Area Rapid Ecosystem Analysis



Projection:  
Albers Conformal Conic Equal Area  
Central Meridian: -96°  
Latitude of Origin: 23°  
1st Standard Parallel: 29°30' 00"  
2nd Standard Parallel: 45°30' 00"  
Datum: North American Datum of 1983

Image Data: National Land Cover Data 1992  
30-meter resolution  
Source: U.S. Geological Service (USGS)